

Dataset Expocode 33RO20160216

Primary Contact **Name:** Sullivan, Kevin
Organization: NOAA/AOML CIMAS
Address: 4301 Rickenbacker Causeway, Miami, FI 33149
Phone: (305) 361-4382
Email: kevin.sullivan@noaa.gov

Investigator **Name:** Wanninkhof, Rik
Organization: NOAA/Atlantic Oceanographic & Meteorological Laboratory
Address: 4301 Rickenbacker Causeway, Miami FI, 33149
Phone: 305-361-4379
Email: Rik.Wanninkhof@noaa.gov

Investigator **Name:** Pierrot, Denis
Organization: NOAA/Atlantic Oceanographic & Meteorological Laboratory
Address: 4301 Rickenbacker Causeway, Miami FI, 33149
Phone: 305-361-4441
Email: Denis.Pierrot@noaa.gov

Dataset **Funding Info:** NOAA Climate Program Office
Initial Submission (yyyymmdd): 20161018
Revised Submission (yyyymmdd): 20170111

Campaign/Cruise **Expocode:** 33RO20160216
Campaign/Cruise Name: RB1602
Campaign/Cruise Info: AOML_SOOP_CO2, TAO 140W-125W
Platform Type:
CO2 Instrument Type: Equilibrator-IR
Survey Type: Research Cruise
Vessel Name: R/V Ronald H. Brown
Vessel Owner: NOAA
Vessel Code: 33RO

Coverage **Start Date (yyyymmdd):** 20160216
End Date (yyyymmdd): 20160316
Westernmost Longitude: 158 W
Easternmost Longitude: 119.8 W
Northernmost Latitude: 25.8 N
Southernmost Latitude: 8 S
Port of Call: Pearl Harbor, HI
Port of Call: San Diego, CA

Variable **Name:** xCO2_EQU_ppm
Unit: ppm
Description: Mole fraction of CO2 in the equilibrator headspace (dry) at equilibrator temperature (ppm)

Variable **Name:** xCO2_ATM_ppm
Unit: ppm
Description: Mole fraction of CO2 measured in dry outside air (ppm)

Variable **Name:** xCO2_ATM_interpolated_ppm
Unit: ppm
Description: Mole fraction of CO2 in outside air associated with each water analysis. These values are interpolated between the bracketing averaged good xCO2_ATM analyses (ppm)

Variable	Name: PRES_EQU_hPa Unit: hPa Description: Barometric pressure in the equilibrator headspace (hPa)
Variable	Name: PRES_ATM@SSP_hPa Unit: hPa Description: Barometric pressure measured outside, corrected to sea level (hPa)
Variable	Name: TEMP_EQU_C Unit: Degree C Description: Water temperature in equilibrator (°C)
Variable	Name: SST_C Unit: Degree C Description: Sea surface temperature (°C)
Variable	Name: SAL_permil Unit: ppt Description: Sea surface salinity on Practical Salinity Scale (o/oo)
Variable	Name: fCO2_SW@SST_uatm Unit: µatm Description: Fugacity of CO2 in sea water at SST and 100% humidity (µatm)
Variable	Name: fCO2_ATM_interpolated_uatm Unit: µatm Description: Fugacity of CO2 in air corresponding to the interpolated xCO2 at SST and 100% humidity (µatm)
Variable	Name: dfCO2_uatm Unit: µatm Description: Sea water fCO2 minus interpolated air fCO2 (µatm)
Variable	Name: WOCE_QC_FLAG Unit: None Description: Quality control flag for fCO2 values (2=good, 3=questionable)
Variable	Name: QC_SUBFLAG Unit: None Description: Quality control subflag for fCO2 values, provides explanation when QC flag=3
Sea Surface Temperature	Location: Bow thruster room, before sea water pump, ~5 m below water line. Manufacturer: Seabird Model: SBE-21 Accuracy: 0.01 (°C if units not given) Precision: 0.001 (°C if units not given) Calibration: Factory calibration Comments: Manufacturer's Resolution is taken as Precision; Maintained by ship.
Sea Surface Salinity	Location: Attached to underway system at sea water input. Manufacturer: Seabird Model: SBE 45 Accuracy: ± 0.005 o/oo Precision: 0.0002 o/oo Calibration: Factory calibration Comments: Manufacturer's Resolution is taken as Precision

Atmospheric Pressure

Location: On bulkhead exterior on the port side of the radio room aft of the bridge at ~14 m above the sea surface.
Normalized to Sea Level: yes
Manufacturer: Vaisala
Model: PTB330
Accuracy: ± 0.2 hPa (hPa if units not given)
Precision: ± 0.08 hPa (hPa if units not given)
Calibration: Factory calibration
Comments: Manufacturer's resolution is taken as precision. Maintained by ship.

Atmospheric CO2

Measured/Frequency: Yes, 5 readings in a group every 3.5 hours
Intake Location: Bow tower ~10 m above the sea surface.
Drying Method: Gas stream passes through a thermoelectric condenser (~5 °C) and then through a Perma Pure (Nafion) dryer before reaching the analyzer (90% dry).
Atmospheric CO2 Accuracy: ± 0.5 μ atm in fCO2_ATM
Atmospheric CO2 Precision: ± 0.01 μ atm in fCO2_ATM

Aqueous CO2 Equilibrator Design

System Manufacturer:
Intake Depth: 5 meters
Intake Location: Bow
Equilibration Type: Spray head above dynamic pool, with thermal jacket
Equilibrator Volume (L): 0.95 L (0.4 L water, 0.55 L headspace)
Headspace Gas Flow Rate (ml/min): 70 - 150 ml/min
Equilibrator Water Flow Rate (L/min): 1.5 - 2.0 L/min
Equilibrator Vented: Yes
Equilibration Comments: Primary equilibrator is vented through a secondary equilibrator.
Drying Method: Gas stream passes through a thermoelectric condenser (~5 °C) and then through a Perma Pure (Nafion) dryer before reaching the analyzer (90% dry).

Aqueous CO2 Sensor Details

Measurement Method: IR
Method details: details of CO2 sensing (not required)
Manufacturer: LI-COR
Model: 6262
Measured CO2 Values: xco2(dry)
Measurement Frequency: Every 140 seconds, except during calibration
Aqueous CO2 Accuracy: ± 2 μ atm in fCO2_SW
Aqueous CO2 Precision: ± 0.01 μ atm in fCO2_SW
Sensor Calibrations:
Calibration of Calibration Gases: The analyzer is calibrated every 3.5 hours using field standards that were calibrated with primary standards that are directly traceable to the WMO scale. Ultra-High Purity air (0.0 ppm CO2) and the high standard are used to zero and span the LI-COR analyzer.
Number Non-Zero Gas Standards: 4
Calibration Gases:

Std 1: CA04957, 282.55 ppm, owned by ESRL, used every ~3.5 hours.
Std 2: CC105863, 380.22 ppm, owned by ESRL, used every ~3.5 hours.
Std 3: CB09696, 453.04 ppm, owned by ESRL, used every ~3.5 hours.
Std 4: CB09032, 539.38 ppm, owned by ESRL, used every ~3.5 hours.
Std 5: 0.00 ppm, owned by AOML, used every ~20.0 hours.
Comparison to Other CO2 Analyses:

Comments:**Method Reference:**

Pierrot, D., C. Neil, K. Sullivan, R. Castle, R. Wanninkhof, H. Lueger, T. Johannessen, A. Olsen, R. A. Feely, and C. E. Cosca (2009), Recommendations for autonomous underway pCO₂ measuring systems and data reduction routines, Deep-Sea Res II, 56, 512-522.

**Equilibrator
Temperature Sensor**

Location: Inserted into equilibrator ~5 cm below water level

Manufacturer: Hart

Model: 1521

Accuracy: 0.025 (°C if units not given)

Precision: 0.01 (°C if units not given)

Calibration: Factory calibration

Comments: Resolution is taken as Precision.

**Equilibrator
Pressure Sensor**

Location: Attached to equilibrator headspace. Differential pressure reading from Setra 239 attached to the equilibrator headspace is added to the pressure reading from the LICOR, which is measured by an external Setra 270 connected to the exit of the analyzer.

Manufacturer: Setra

Model: 270

Accuracy: 0.15 (hPa if units not given)

Precision: 0.015 (hPa if units not given)

Calibration: Factory calibration

Comments: Manufacturer's Resolution is taken as Precision.

**Additional
Information**

Suggested QC flag from Data Provider: NA

Additional Comments: The analytical system performed well during most of this cruise. The appending of SCS data to the CO₂ data records was not as consistent as during other cruises, so the TSG21 Temperature in the ship's ELG files was used as SST. Small gaps in the ATM pressure values recorded with the CO₂ data were filled with values from the ship's ELG files. The CO₂ analytical system shutdown for repair after noon on YD 172. When the system was restarted the equilibrator temperature sensor was not powered. For the 396 analyses during those ~20 hrs, the EQU temperature was estimated by subtracting 0.06 deg C from the temperature measured by the Oxygen Optode attached to the CO₂ system. For 10897 analyses the average difference between the temperature measurements in the equilibrator and by the optode was 0.059 (+/-0.031) degree Celsius. Starting at ~09:00 on 26 Feb, the gas flow during ATM analyses was very low. Good ATM gas flow was reestablished at ~14:30 on 28 Feb. No ATM analyses were processed during this interval. Additional raw data files were recovered, processed, and submitted in 2017. Original Data Location: http://www.aoml.noaa.gov/ocd/ocdweb/brown/brown_introduction.html

Citation for this Dataset:

Other References for this Dataset: